TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

IMPORTANT:

THIS DRAWING SHALL BE USED IN COMBINATION WITH THE GENERAL NOTES AT THE BEGINNING OF STANDARDS MD 104.00.

NOTES:

MOUNT SIGNS ON BOTH SIDES OF THE WORK AFFECTED ROADWAY ON DIVIDED HIGHWAYS.

ON TWO-LANE, TWO-WAY ROADWAYS, CLOSE THE LANE ADJACENT TO THE EXCAVATED AREA; CONTROL TRAFFIC WITH FLAGGING OPERATION IN CONFORMANCE WITH STANDARD MD 104.02-01.

DROP-OFF SHALL BE PROVIDED WITH A 4:1 OR FLATTER SLOPE FILLET WEDGE AT ALL TIMES WHILE NO WORK IS BEING PERFORMED. SEE AND IMPLEMENT STANDARD MD 104.90.

KEY:






 ∞

ARROW PANEL

WORK SITE



SPECIFICATION CATEGORY CODE ITEMS

104

APPROVED

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

Administration

Director - OFFICE OF INAFFIC AND SAFETY

APPROVAL • SHA
REVISIONS

APPROVAL • FEDERAL
HIGHWAY ADMINISTRATION
APPROVAL 9-10-96
REVISED 10-1-01
REVISED

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

PAVEMENT EDGE DROP-OFF, GREATER THAN 5 INCHES WITH AN ADJACENT LANE CLOSURE

STANDARD NO.

MD 104.91-02